

Light Powered NSF Remote Reading Thermometers

25SD



CASE:	1" x 4" Surface Mounting, Black or White
MASK:	Black or Silver Mask / Custom logo on request
RANGE:	40-0-160°F or 40-0-70°C factory set
DISPLAY:	3/8" LCD
LIGHT RATING:	30 Lux to 50,000 Lux
SENSOR LENGTH:	3 Ft. or 5 Ft.
ENVIRONMENT:	Splash Proof (optional black or white gasket)
ACCURACY:	NSF Accuracy for food zone applications. (±2°F between -20 to +60°F)

56SD



CASE:	2" Round Back (56mm Square Front)
MOUNTING:	Front Flange or U-Clamp
RANGE:	40-0-230°F and 40-0-110°C (field switchable)
DISPLAY:	3/8" LCD (1/10° display up to 200°F)
LIGHT RATING:	15 Lux to 50,000 Lux
SENSOR LENGTH:	3 Ft. or 5 Ft.
ENVIRONMENT:	Waterproof from Front
OPTIONS:	U-Clamp Case, Model 56SD-U
ACCURACY:	NSF Accuracy for food zone applications. (1% of reading ±1°F or ±.5°C)

72SD



CASE:	2 1/2" Round Back (72mm Square Front)
MOUNTING:	Front Flange or U-Clamp
RANGE:	40-0-160°F or 40-0-70°C, factory set
DISPLAY:	1/2" LCD - 1/10° display
LIGHT RATING:	30 Lux to 50,000 Lux
SENSOR LENGTH:	3 Ft. or 5 Ft.
ENVIRONMENT:	Splash Proof (optional gasket)
OPTIONS:	U-Clamp Case, Model 72SD-U
ACCURACY:	NSF Accuracy for food zone applications. (±2°F between -20 to +60°F)

20SD



CASE:	2" Round, Stainless Steel
RANGE:	40-0-160°F or 40-0-70°C, factory set
DISPLAY:	3/8" LCD
LIGHT RATING:	50 Lux to 50,000 Lux
BATTERY ASSIST:	15 LUX @ 10 years
SENSOR LENGTH:	3 Ft. or 5 Ft.
ENVIRONMENT:	Splash Proof from the Front
ACCURACY:	NSF Accuracy for food zone applications. (±2°F between -20 to +60°F)